

EASYCAP PROPACK VCI

The anticorrosion cap!



Easycap Propack VCI is a particular application of **Propack VCI**

coextruded film specifically conceived to solve the problems of protruding metal parts.

The **Propa-film VCI** that makes up **Easycap** is made by adding the

Propack VCI additive to the polythene mass during the coextrusion of the three-layer film. The inner layer is for immediate protection, the middle layer is a reserve for long-term protection, whereas the outer layer acts as a barrier and contains the protective substance.

Simple, effective and rapid, **Easycap Propack VCI** features an elastic band at its open end, which makes it like a "shower cap" capable of covering any irregularly shaped object without problems and assuring protection also in situations where this would be difficult or even impossible with other products. Available in different sizes, **Easycap Propack VCI** is especially recommended for protecting brake disks, small motors, flywheels, cylinder heads and variously shaped projections.

Unlike old oiling and greasing systems, **Easycap** is practical, low cost and pollutes less.

The manufactured good is ready for use as soon as the packaging is opened and no pickling is required.

PROPACK[®]
Anticorrosion



EASYCAP PROPACK VCI



Test	U.M.	Method	100 my
Density	g/cm ²	ASTM D1505/ ISO/R 1183	0.92÷0.93
MFI	G/10min	ISO 1133	0.70÷1.00
Thickness	μ	ISO 4593	100 ± 10%
Width	mm	house by comparison	nominal -0+2%
Length	m	house by comparison	nominal -0+8%
Ultimate strength machine direction (MD)	N/mm ²	ASTM D882	>21
Ultimate strength cross direction (TD)	N/mm ²	ASTM D882	>19
Ultimate elongation machine direction (MD)	%	ASTM D882	>270
Ultimate elongation cross direction (TD)	%	ASTM D882	>310
Fire point	°C	/	>350

Bag Dimension (cm)	Elastic dimension (cm)	Maximum elastic extension (cm)
50x60	16 ±10%	40 ±10%



The anticorrosion cap!



Via Genova, 5/B - 10098 Rivoli (Turin) Italy
 Tel +39 011 9507788 - Fax -39 011 9507808
 www.propack.eu - export@propack.eu